

Industrial Stationary

# AIR COMPRESSORS Jenny®



# Base Plate Mounted Compressors

## Standard Features

- Heavy-duty single or two stage cast iron compressor pump  
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Oil sight glass (Except F-pump)
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard



F34A-B



K15A-B

## Single Stage

Model	Pump	HP	Power Supply	125 PSI		
				Pump RPM	CFM Disp	Del'd Air
F12A-B	F	1/2	115 Volt (through 2 HP) or 230 Volt 1 Phase	680	3.4	2.2
F34A-B		3/4		1080	5.3	3.1
K1A-B	K	1		560	6.2	4.0
K15A-B		1-1/2		870	9.8	6.2
K2A-B		2	208, 230, 460 or 575 Volt 3 Phase	1140	13.1	8.0
GC2A-B	GC	2		480	13.1	9.1
GC3A-B		3		770	21.0	14.0
GC5A-B		5		1020	27.8	17.8
J5A-B	J			780	28.7	19.0

## Electric

- Auto Start/Stop control with pressure unloader set at 105-125 PSI (single stage) or 145-175 PSI (two stage)
- Control group (not mounted)
- Check valve
- Magnetic starter is included on all 5 HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection

## Two Stage

Model	Pump	HP	Power Supply	175 PSI		
				Pump RPM	CFM Disp	Del'd Air
GT2B-B	GT	2	115 Volt (through 2 HP) or 230 Volt 1 Phase	450	9.1	7.1
GT3B-B		3		660	13.4	10.7
W3B-B	W			440	12.2	10.7
GT5B-B	GT	5	208, 230, 460 or 575 Volt 3 Phase	900	18.3	15.2
W5B-B	W			760	21.1	17.5
U75B-B	U	7-1/2		610	38.0	27.2
U10B-B		10	208, 230, 460 or 575 Volt 3 Phase Only	710	43.6	35.2
T15B-B	T	15		520	72.4	56.5
T20B-B		20		670	92.6	72.2
T25B-B		25		780	107.0	83.0



GC3A-B



W5B-B

## Options

- Constant run control
- Dual control
- Magnetic starter
- Air line filter
- Lubricator
- Aftercooler
- Dryer
- Oil sight glass (F-pump)
- Other pressures available upon request

# Base Plate Mounted Compressors

- Powder coated, extra heavy steel base plate
- Large canister intake filter with replaceable filter elements
- Pressure relief safety valve
- Pressure gauge
- Oil sight glass



T25KGB-B

## Gas

- Constant run control set at 105-125 PSI (single stage) or 145-175 PSI (two stage)
- High quality pilot valve
- Pneumatic throttle idle control
- Honda GX Series OHV Engine or Kohler OHV V-Twin Engine



GT11HGB-B



K5HGA-B

## Single Stage

Model	Pump	HP	Drive	Pump RPM	CFM Disp	Del'd Air
K5HGA-B	K	5.5	Recoil	1285	14.2	8.6
GC8HGA-B	GC	8	Start	890	24.6	16.0
GC11HGA-B		11	Electric	1070	28.6	18.3
J11HGA-B	J		Start	865	31.8	20.9

125 PSI

## Two Stage

Model	Pump	HP	Drive	Pump RPM	CFM Disp	Del'd Air
GT5HGB-B	GT	5.5	Recoil	570	14.2	9.1
GT8HGB-B		8	Start	820	19.2	15.4
GT11HGB-B		11	Electric	985	28.6	16.3
W11HGB-B	W			760	21.1	17.6
U18HGB-B	U	18		800	49.8	34.7
T25KGB-B	T	25		625	86.4	67.3

175 PSI

## Options

Air line filter ■ Lubricator ■ Electric start  
 Other pressures available upon request  
 Other engine options available upon request

# Electric Stationary Compressors

## Standard Features

- Heavy-duty single or two stage cast iron compressor pump  
Made in Somerset, PA USA
- Splash lubricated
- Oil sight glass (Except F-pump)
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- Tank gauge
- Tanks are powder coated and ASME certified
- 60 gallon tanks and larger are ASME National Board certified
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor starting
- Pressure relief safety valve



F13A-17



K15A-30



GC3A-60V



K15A-30V

## Single Stage

Single Stage				Power Supply	125 PSI		
Model	Pump	HP	Tank Gallon		Pump RPM	CFM Disp	Del'd Air
F12A-17	F	1/2	17	115 Volt (through 2 HP) or 230 Volt 1 Phase	680	3.4	2.2
F34A-17		3/4			1080	5.3	3.1
F34A-30			K		1	560	6.2
K1A-30	1-1/2	870			9.8	6.2	
K15A-30		60			1140	13.1	8.0
K15A-60	30						
K2A-30	2	60					
K2A-60		30			480	13.1	9.1
GC2A-30		60					
GC2A-60	3	30	770				
GC3A-30		60					
GC3A-60		5			60	1020	27.8
GC5A-60	80						
GC5A-80	J		60		780		
J5A-60		80					
J5A-80							

## Options

- Constant run ■ Dual control ■ Low oil level switch  
Automatic tank drain ■ Magnetic starter  
Control circuit transformer ■ Vertical tank  
Air line filter ■ Lubricator  
Aftercooler ■ Dryer ■ Oil sight glass (F-pump)  
Other pressures and tank sizes available upon request

# Electric Stationary Compressors

- Auto Start/Stop control with pressure unloader set at 105-125 PSI (single stage) or 145-175 PSI (two stage)
- Magnetic starter is included on all 5HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- Alternator and magnetic starter are standard on all duplex models



U10B-120

GT5B-80V



T25B-240



W5B-80

## Two Stage

Model	Pump	HP	Tank Gallon	Power Supply	175 PSI Pump RPM	CFM Disp	Del'd Air
GT2B-60	GT	2	60	115 Volt (through 2 HP) or 230 Volt 1 Phase	450	9.1	7.1
GT2B-80			80				
GT3B-60		3	60		660	13.4	10.7
GT3B-80			80				
W3B-60	W	3	60		440	12.2	10.7
W3B-80			80				
GT5B-60	GT	5	60		900	18.3	15.2
GT5B-80			80				
GT5B-120			120				
W5B-60	W	5	60	208, 230, 460 or 575 Volt 3 Phase			
W5B-80			80		760	21.1	17.5
W5B-120			120				
U75B-80	U	7-1/2	80		610	38.0	27.2
U75B-120			120				
U10B-80		10	80		710	43.6	35.2
U10B-120			120				
T15B-120	T	15	120	208, 230, 460 or 575 Volt 3 Phase Only	520	72.4	56.5
T15B-240			240				
T20B-120		20	120		670	92.6	72.2
T20B-240			240				
T25B-120		25	120		780	107.0	83.0
T25B-240			240				

## Duplex Single Stage

Model	Pump	HP	Tank Gallon	Power Supply	175 PSI Pump RPM	CFM Disp	Del'd Air
2(K15A)-60	K	3	60	115 Volt (through 2 HP) 230 Volt 1 Phase	870	19.6	12.4
2(GC5A)-80	GC	10	80		1020	55.6	35.6

## Two Stage

Model	Pump	HP	Tank Gallon	Power Supply	175 PSI Pump RPM	CFM Disp	Del'd Air
2(GT5B)-120	GT	10	120	208, 230, 460 or 575 Volt 3 Phase	900	36.6	30.4
2(W5B)-120	W				762	42.4	35.0
2(U10B)-120	U	20	240	208, 230, 460 or 575 Volt 3 Phase Only	710	87.2	70.4
2(U10B)-240					780	214.0	166.0
2(T25B)-240	T	50					

# Climate Control Compressors

## Standard Features

- Heavy-duty cast iron compressor pump  
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil
- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- Tanks are powder coated and ASME certified
- 60 gallon tanks and larger are ASME National Board certified
- Oil sight glass (Except F-pump)
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor starting
- Tank gauge
- Pressure relief safety valve
- Auto Start/Stop control with pressure unloader set at 75-100 PSI
- Magnetic starter is included on all 5HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- Alternator and magnetic starter standard on all duplex models

## Simplex Single Stage

Single Stage				Tank Gallon	Power Supply	Pump RPM	CFM Disp	Del'd Air	
Model	Pump	HP	590			2.9	1.7		
F12C-30C	F	1/2	30			115 Volt (through 2 HP) 230 Volt 1 Phase	420	4.8	2.7
KC34C-30C	KC	3/4					520	5.9	3.7
K1C-30C	K	1							
Two Stage						100 PSI			
GT2C-60C	GT	2	60	208, 230 460, or 575 Volt 3 Phase	540	11.0	9.1		
W3C-80C	W	3	80		480	13.5	11.6		
W5C-80C		5			760	21.5	17.7		
U75C-80C	U	7-1/2		80	208, 230 460, or 575 Volt 3 Phase Only	610	38.0	28.5	
U10C-80C		10	710			43.6	35.2		
T15C-120C	T	15	120	520		72.4	57.5		
T20C-120C		20		670		92.6	73.5		
T25C-120C		25		780		107.0	85.0		

## Duplex Single Stage

Single Stage				Power Supply	Pump RPM	CFM Disp	Del'd Air
Model	Pump	HP	Tank Gallon		590	5.8	3.4
2(F12C)-30C	F	1	30		420	9.6	5.4
2(KC34C)-60C	KC	1-1/2	60		520	11.8	7.4
2(K1C)-60C	K	2		115 Volt (through 2 HP) 230 Volt 1 Phase	100 PSI		
Two Stage				208, 230 460, or 575 Volt 3 Phase	540	22.0	18.2
2(GT2C)-60C	GT	4	60		480	27.0	23.2
2(W3C)-80C	W	6	80		760	43.0	35.4
2(W5C)-80C		10					
2(U75C)-120C	U	15	120	208, 230, 460 or 575 Volt 3 Phase Only	610	76.0	57.0
2(U10C)-120C		20			710	87.2	70.4
2(T15C)-240C	T	30	240		520	144.8	115.0
2(T20C)-240C		40			670	185.2	147.0
2(T25C)-240C		50			780	214.0	170.0

## Options

- Low oil level switch ■ Automatic tank drain ■ ASME National Board tank  
Magnetic starter ■ Control circuit transformer ■ Vertical Tank  
Air line filter ■ Lubricator ■ Aftercooler ■ Dryer ■ Oil sight glass (F-pump)

K1C-30C



W5C-80C



2GT2C-60C

# Fire Sprinkler Stationary Compressors

## Base Plate Mounted

### Standard Features

- Heavy-duty single stage cast iron compressor pump  
Made in Somerset, PA USA
- Splash lubricated
- Belt driven with a large flywheel for extra cooling and easier start-up
- Each unit is filled with Jenny Ultimate Blue Compressor Pump Oil

- Directional air shroud for reduced pump temperatures
- Totally enclosed heavy-duty belt guard
- Powder coated, extra heavy steel base plate
- Large canister intake filter with replaceable filter elements
- Magnetic starter is included on all 5HP and larger units
- Industrial/Commercial grade UL Listed electric motor
- Thermal overload motor protection
- Oil sight glass (Except F-pump)



### Base Mounted System Size

Maximum Gallons  
in system to be  
pumped to 40 PSI  
in 30 Minutes

	Model	Pump	HP	Power Supply	Pump RPM	CFM del'd @ 40 PSI	Optional Auto Control Group
220	F13S-BS		1/3	115 Volt (through 2 HP) or 230 Volt 1 Phase	670	2.9	ACGF
290	F12S-BS	F	1/2		950	3.8	
350	F34S-BS		3/4		1200	4.4	
425	K34S-BS	K			520	5.3	ACGK
480	F1S-BS	F	1	208, 230, 460 or 575 Volt 3 Phase	1430	6.0	ACGF
600	K1S-BS				790	7.4	ACGK
885	K15S-BS	K	1-1/2		1140	10.9	
985	K2S-BS		2		1280	12.4	
1215	G2S-BS				630	15.1	ACGD
1775	G3S-BS	G	3		950	21.8	
1950	GC5S-BS		5		1030	24.2	ACGJ
2115	J5S-BS	J			830	26.0	

### Tank Mounted/30 Gallon

220	F13S-30S		1/3	115 Volt (through 2 HP) 230 Volt 1 Phase	670	2.9
290	F12S-30S	F	1/2		950	3.8
350	F34S-30S		3/4		1200	4.4
425	K34S-30S	K			520	5.3
480	F1S-30S	F	1	208, 230, 460 or 575 Volt 3 Phase	1430	6.0
600	K1S-30S				790	7.4
885	K15S-30S	K	1-1/2		1140	10.9
985	K2S-30S		2		1280	12.4
1215	G2S-30S				630	15.1
1775	G3S-30S	G	3		950	21.8
1950	GC5S-30S	GC	5		1030	24.2
2115	J5S-30S	J			830	26.0

## Tank Mounted

### Additional Standard Features

- Tanks are powder coated and ASME certified
- Protectively mounted fittings
- Manual tank drain(s)
- Large canister intake filter with replaceable filter elements
- Special unloading valves to assist in motor starting
- Tank gauge
- Pressure relief safety valve
- Auto Start/Stop control with pressure unloader set at 30-40 PSI

### Options

- ASME National Board tank
- Magnetic starter
- Oil sight glass (F-pump)
- 17 gallon tank
- Vertical tank
- Low oil level switch
- Automatic tank drain
- Air line filter
- Aftercooler
- Dryer
- Control Group



# AIR COMPRESSORS **Jenny**

**Jenny Products, Inc.**

850 North Pleasant Avenue  
Somerset, PA 15501-1069

Phone 814-445-3400

Fax 814-445-2280

[www.jennyproductsinc.com](http://www.jennyproductsinc.com)

[www.jennycompressor.com](http://www.jennycompressor.com)