

Technical Specs

- Item Tubeaxial Fan with Motor and Drive Package
 - Drive Type Belt-Drive
 - Blade Dia. 24"
 - CFM @ 0.000-In. SP 9112
 - CFM @ 0.125-In. SP 8856
 - CFM @ 0.250-In. SP 8573
 - CFM @ 0.500-In. SP 7983
 - CFM @ 0.750-In. SP 7290
 - CFM @ 1.000-In. SP 6445
 - Sones @ 0.250-In. SP @ 5 Ft. 43
 - Motor HP 2
 - Max. BHP 1.98
 - Fan RPM 1688
 - Motor Enclosure Totally Enclosed Fan Cooled
 - Phase 3
 - Voltage 208-230/460
 - Max. Motor Height 10"
 - Shaft Dia. 1"
 - Number of Blades 6
 - Full Load Amps 6.0-5.4/2.7
 - Motor Type 3-Phase
 - Max. Inlet Temp. 200 Degrees F
 - Max. Ambient Temp. 104 Degrees F
 - Bearing Type BALL
-
- Mounting Position Vertical/Horizontal
 - Housing Material Steel
 - Housing Finish Baked Enamel
 - Blade Material Spark Resistant Aluminum
 - Hz 60
 - Motor RPM 1735
 - Height 37-1/4"
 - Width 26-7/8"
 - Max. Depth 18"
 - Housing Dia. w/Mtg. Flange 27"
 - Housing Dia. w/o Mtg. Flange 24-5/16"
 - Inlet Dia. 24-7/16"
 - Outlet Dia. 24-7/16"
 - Assembled/Unassembled Unassembled
 - Bolt Circle Dia. 25-3/4"
 - Replacement Fan Blade Stock No. 4C664
 - Companion Flange Stock No. 3C436
 - Standards AMCA
 - Includes Belt guard
 - Dimension A 27"
 - Dimension B 16-3/4"
 - Dimension C 24-5/16"
 - Dimension D 18"
 - Dimension E 7/16"

