Under Hoist Oil Drains



Features: Models 8G-Drain and 18G-Drain

- Spout for evacuation
- ◆ Hand grips top and bottom for ease in evacuation
- ◆ Four 3 ½" ball bearing wheels
- ♦ Height adjusts from 48 -71"
- Translucent polyethylene body allows easy viewing of fluid level
- ▶ 18" funnel with non-corrosive telescoping tube
- ♦ ¾"evacuation valve (18 gallon model only)

STANDS





Features: Self-Extracting 21G Oil Drain

- ◆ 14" diameter funnel
- 8' evacuation hose
- ◆ 21 gallon capacity
- Pressure gauge included
- ◆ Sight glass

Transmission Jacks





Features: Model 3190-TJ

- ◆ Two-stage telescopic ram
- Universal head allows 42° forward tilt, 46° back tilt and 12° side tilt
- Fully adjustable universal saddle with spring loaded corner brackets allows easy tool-free adjustment
- Foot operated pump allows use of both hands to position and align saddle with transmission

Features: Model 2158-TJ

- For use with in-ground and above-ground lifts
- ♦ Single-stage telescopic ram
- Wide base for stability
- Foot operated pump allows use of both hands to position and align saddle with transmission

| Specifications | 2158-TJ | 3190-TJ |
|-----------------|------------|------------|
| Capacity | 1,100 lbs. | 1,100 lbs. |
| Low height | 45" | 33 ½" |
| High height | 71" | 72 ½" |
| Shipping weight | 97 lbs. | 219 lbs. |