Atlanta 11/27/17

Offer n°	15.RLS
Page n°	4

PARTS WASHING MACHINE-SINGLE STAGE, WITH 1 PUMP

Series: Impact Model. HP-25





MACHINE DESCRIPTION X81 L-90

Include:

1. AISI 304 construction	
2. Manual opening lid.	
3. Foot pedal pump operation	
4. Electrical heaters	
5. Cartridge filter	
6. Electrical box	
7. Water level shut off	

Automatic Cycle Description

1.	Manual parts loading	(operator)
2.	Manual lid closing	(operator)
3.	Start cycle	(operator)
4.	Manual wash cycle	(operator)
5.	Manual open lid	(operator)
6.	Manual parts unloading	(operator)

Machine Technical Data

Maximum load height	19 ½ "
Maximum load width	31"
Maximum load length	23 ½
Maximum load weight	350 lbs.

Wash tank

Volume	35 gal
Pump horse power	2 HP
Pump psi	850 psi
Flow rate pumps	3.7 gpm.
Heater	3 KW
Drain	1"

Electrical data

Used electrical power	4 kW
Voltage	220V 1Ph 60Hz
Low voltage tension	24V ac

Machine footprint

Width	43"
Height with open lid	77"
Dry weight	309 lbs.



Machine Technical Description

Construction: The machine body is constructed in AISI 304 stainless steel.

Water circuit: A piston driven pump (850 psi) pumps the water solution through the spray wand.

Cartridge filter: The water solution continuously flows cartridge filter (50 microns).

Electrical heater: The water solution is heated by a stainless steel heater, which is controlled by thermostat to regulate the water temperature.

Foot Pedal Operation: The pump is activated by foot pedal switch.

Water level shut of: The unit is equipped with a liquid level float to stop the machine, when the liquid level is low.

Manual lid: Two gas struts assist the opening and closing of the machine lid.

Electro mechanic electrical box: IP 55, painted RAL 7032