

# ***HEM Double Miter Band Saws***

## **320 BSA**



### **Semi-Automatic Saw**

Fully Hydraulic with Feed Rate & Cutting Pressure

**Capacity:** 12.6" x 9.1" H @ 90° (10.8" Round)  
7.9" x 3.9" H @ 45° R • 7.3" x 8.7" H @ 45° L • 4.7" x 8.7" H @ 60° L

**Blade Size:** 1" x 119" x .035" **Motor:** 3 HP (440V 3-Phase)

Dual 45° Miter, One-Way 60° Miter, Variable Speed Motor,  
Hard-Stop Measuring Device, Moveable Control Console w/ 40" Umbilical,  
Rugged 3/16" Steel Base, Miter Scale, Heavy-Duty Sealed Pivot Bearing Point,  
Blade Speed & Height Set from Control Panel, Full Capacity Cutting Surface  
Flood Coolant System, Optional Inbound or Outbound Roller Tables

**HEM<sup>®</sup> & SAW**  
—The saw that cuts straight.—

[www.hemsaw.com](http://www.hemsaw.com)

P.O. Box 1148, Pryor, OK 74362 • Sales Rep. - Rick Gwartney (918) 691-8653  
Phone: (918) 825-4821 Fax: (918) 825--4824 • E-Mail: [info@hemsaw.com](mailto:info@hemsaw.com)