SEMI-AUTOMATIC TIRE **CHANGERS** This model is a great TC-530 Semi-automatic Tire changer **Features:**

- · Swing arm style
- Manual operation of mount/demount tool
- Four pneumatic clamps and double acting cylinders
- Side mounted bead breaker
- Bead seating inflation jets are integrated in the clamping jaws insuring quick and safe inflation
- Includes water separator, lubricator and air pressure regulator



Features:


- Swing arm design
- Handles tires to 47" diameter and rim widths to 15"
- · Bead seating inflation jets are integrated in the clamping jaws insuring quick and safe inflation
- Twin clamping cylinders provide more power to hold the most difficult rims
- Conveniently located and powerful bead breaker
- No scratching. Machine never contacts rim eliminating accidental damage
- Large diameter hex mount /demount shaft for extra rigidity
- Pressure limiter, water separator and oiler are standard

This model has power to spare and a 26" x 26" square turntable that can handle wheel diameters up to 47" with ease.

Specifications:	TC-530	TC-950
Max wheel diameter	38"	47"
Max wheel width	3"-12"	3"-15"
Rim diameter inside	12"- 23"	15" - 28"
Rim diameter outside	10"- 20"	13"- 24"
Working pressure	8-10 bar	8-10 bar
Power supply	110 vac	1½ hp 110 vac
Bead breaker	2500 kg	2500 kg

Optional: Motorcycle adapters





Quickly attaches over clamps to accommodate motorcycle wheels.